

## SATA SLIM J200



FCC E RoHS

## FEATURES

- High Performance
- S.M.A.R.T. & i-S.M.A.R.T. Supported
- Built-in hardware BCH ECC
- Bad block management
- Excellent data transfer performance

R: 220MB  
W: 200MB

S.M.A.R.T

Budget  
friendlyWear  
LevelingMDMA  
UDMA

## Specifications

Connector Type	Standard 7+15 Pin SATA Connector
Flash Type	SLC ( single level cell)
Density	8GB, 16GB, 32GB, 64B, 128GB
Interface	SATA II, SATA I, PIO 0~4, MDMA 0~2, UDMA 0~6
Sustained R/W Performance	Read : 220MB/sec (max.) Write : 200 MB/sec (max.)

## Environmental

DC Input	+5V DC $\pm 5\%$
Power consumption (Max.)	Read: 300mA Write: 350 mA Idle: 150 mA
Operating Temperature	0°C~+70°C (Standard Grade) -40°C~+85°C (Industry Grade)
Storage Temperature	-55°C~+95°C
Humidity	Relative Humidity: 10-95%, non-condensing
Endurance	100,000 program/erase cycles
MTBF	> 3,000,000 hours
Certification	CE, FCC, RoHS
Warranty	5 years

## Mechanicals

Dimension (W x L x H)	54mm x 39mm x 6.5 mm
Weight	14g $\pm$ 1g
Vibration	7 Hz to 2K Hz, 3 axes
Shock	Duration: 0.5ms, 1500G, 3 axes


## Health monitoring Tool

S.M.A.R.T.	Supported
i-S.M.A.R.T.	Supported (Utility for Windows, Linux)

## Ordering Information

Capacity	Standard Grade	Industry Grade
8GB	D1SS-08GJ20A <u>C</u> 1ES	D1SS-08GJ20A <u>W</u> 1ES
16GB	D1SS-16GJ20A <u>C</u> 1ES	D1SS-16GJ20A <u>W</u> 1ES
32GB	D1SS-32GJ20A <u>C</u> 1ET	D1SS-32GJ20A <u>W</u> 1ET
64GB	D1SS-64GJ20A <u>C</u> 1ET	D1SS-64GJ20A <u>W</u> 1ET
128GB	D1SS-A28J20A <u>C</u> 1ET	D1SS-A28J20A <u>W</u> 1ET

## Mechanical diagram



Tolerance  $\pm 0.1\text{mm}$

\*The pin assignment, component keep out area of InnoDisk SATA Slim J200 is followed by JEDEC MO297 Specification.